

Byggemål løslensers



Basert på ISO /DIN 2642.
EN1092 PN10 boring -
PP-Flenser type SIMONA

ND	Dim	DY		Antall bolter	M	D1	D i		H	
		PP	Galv				PP	Galv	PP	Galv
15	20	95	95	4	M12	65	27,5	32	12	14
20	25	105	105	4	M12	75	34	38	14	14
25	32	115	115	4	M12	85	42	48	16	16
32	40	140	140	4	M16	100	51	55	18	16
40	50	150	150	4	M16	110	62	66	18	16
50	63	165	165	4	M16	125	78	78	18	16
65	75	185	185	4	M16	145	92	92	18	16
80	90	200	200	8	M16	160	108	108	20	18
100	110	223	220	8	M16	180	128	128	20	18
100	125	223	220	8	M16	180	135	135	20	18
125	140	250	250	8	M16	210	158	155	24	18
150	160	285	285	8	M20	240	178	178	24	18
150	180	285	285	8	M20	240	190	188	24	18
200	200	340	340	8	M20	295	235	225	24	20
200	225	340	340	8	M20	295	238	238	24	20
250	250	403	395	12	M20	350	288	273	30	22
250	280	405	395	12	M20	350	294	294	30	26
300	315	460	445	12	M20	400	338	329	34	26
350	355	505	505	16	M20	460	376	376	42	28
400	400	570	565	16	M24	515	430	430	46	32
500	450	670	615	20	M24	620	517	465	45	38
500	500	670	670	20	M24	620	533	515	45	38
600	560	810	780	20	M27	725	618	575	50	36
600	630	810	835	20	M27	725	645	645	50	36
700	710	912	895	24	M27	840	740	725	49	45
800	800	1026	1015	24	M30	950	843	815	58	53
900	900	1129	1115	28	M30	1050	947	915	62	56
1000	1000	1245	1230	28	M33	1160	1050	1015	70	62
1200	1200		1455	32	M36	1380		1215		68

Mål i kursiv/blått er på profilerte PP løslensers

